

Conformal Coating Thinner

2105

Techspray offers a variety of coating formulas to match field and engineering requirements. Specifications generally depend on the type of protection needed: e.g. thermal, moisture, and static resistance.

Coatings contain Opti/Scan to allow quality control inspection of coverage and evenness of the coating on a PCB. A coated board can be passed under a standard, low-cost UV (short-wave black) light, and the coated areas glow. The brighter the glow, the thicker the coating.





Thinner for all Fine-L-Kote conformal coatings

Techspray coatings can be thinned to meet production requirements using Conformal Coating Thinner (2105).

- Thins most types of conformal coating
- Adjust viscosity for spray systems
- Non-ozone depleting

Product Packaging

2105-G Fine-L-Kote UR Thinner 1 gal 1 units/case



Chemical & Physical Properties	
Appearance	Clear, colorless liquid
Odor	Sweet ester odor
Flash Point	58°F
VOC (EPA)	887 g/l
VOC (CARB)	
Boiling Point	102°C
Density	0.89

Chemical Composition

CHEMICAL NAME	CAS#
n-Propyl acetate	109-60-4





Environmental Policy

Techspray is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Resources

Techspray products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Techspray
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

<u>Europe</u>

ITW Contamination Control BV Saffierlaan 5 2132 VZ Hoofddorp The Netherlands +31 88 1307 400 email: info@itw-cc.com

Countries Outside US

Call to locate a distributor in your country

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.

