



Modular WorkSafe® Light ESD No. 789





Modular Diamond-Plate ESD No. 788



Performance: BETTER

Wearwell Modular ESD mats are ideal for virtually any environment where static discharge is a problem: Computer or microprocessor assembly, Circuit board repair, Manufacturing, etc. The **3' x 3'** size is perfect for individual workstations, yet both products have interlocks on two sides so multiple mats can be snapped together. Designed for comfort, they greatly reduce standing worker fatigue. Both products are 1/2" thick, lightweight, easy to clean and have rounded edges.

This mat must be grounded (use our **15' ground cord**), and employees must either wear **Heel Grinders** or shoes with conductive soles. A **grounding snap** is attached to lower left had corner of **each mat**. And for maximum effectiveness, keep the surface clean.




Stock Size

Part Number	Size
789.12x3x3GRBK	3' x 3'
788.12x3x3GRBK	3' x 3'

Non-Stock Size

Part Number	Size
789.12CustomGRBK	To 15' W x 60' L
788.12CustomGRBK	To 15' W x 60' L

C Custom widths and unique configurations available in 12" increment. Please call for pricing.



Specs

Uses
Compound
Resistivity

Coefficient of Friction /No. 789
Coefficient of Friction /No. 788
Durometer
Tabor Abrasion
Flammability
Thickness
Warranty

Areas at risk for damage from static electricity
SBR/Natural Rubber
RTT - 1×10^5 to 8×10^5 ohms
RTG - 1×10^5 to 8×10^5 ohms
1.0 Dry .85 Wet per ASTM F1677
1.01 Dry .81 Wet per ASTM F1677
75 per ASTM D2240
1% lost @ 1,000 cycles per Fed Std. 191
"A" Rating per MVSS 302
1/2"
1 year, conditional

15' Ground Cord No. 793.15Cord



Use the cord to connect all ESD tabletop and floor mats to a building ground. The solderless terminal can be connected to an electrical outlet using the screw in the outlet cover.

Stock Size

Part Number	Size
793.15Cord	15' cord

Specs

Uses To connect all ESD mats to a building ground
Construction Molded-in male snap fastener on one end and solderless terminal on the other.
Resistivity Integral one megohm resistor (1×10^6 ohm)
Snap Conforms to 10mm snaps

Heel Grinder No. 793.HG

Made for workers wearing insulative shoes, the Heel Grinder allows static electricity to pass from the worker to the ESD matting or flooring. One size "fits all" and the Velcro® loop allows for easy attachment. Allow the fabric strip to touch the workers skin for best performance.



Stock Size

Part Number	Size
793.HG	One Size Fits All

Specs

Uses To allow shoes to conduct static discharge
Construction Two-layer laminated rubber sole with Velcro® loop attachment
Resistivity One megohm resistor (1×10^6 ohm)
Width 1.5"
Thickness 0.060"